



























DETERMINE THE TYPE OF YOUR BB SHELL	**MEASURE THE BB SHELL FRAME WIDTH**	CRANK SPINDLE DIAMETER		**SELECT YOUR BB MODEL**		FULLY ASSEMBLED WIDTH	DETERMINE SPACER USAGE NON-DRIVE SIDE	DRIVE SIDE	**ASSEMBLE BOTTOM BRACKET AS SHOWN BELOW**	DUB CONVERSION AVAILABLE	**TRUVATIV GXP CONVERSION AVAILABLE**
T47 THREADED	68mm	24mm	ROAD		BBT476824SSN (Black) Other colours are available	 91mm	1 x 1mm (BB018-05)	1 x 1mm (BB018-05)	NDS DS 	✗	✓ BBSP109
			MTB		BBT476824SSN (Black) Other colours are available	 96.5mm	1 x 2.5mm (BB018-04)	2 x 2.5mm (BB018-04)	NDS DS 	✗	✓ BBSP109
		30mm	ROAD		BBT476830SSN (Black) Other colours are available	 91mm	1 x 1mm (BB018-05)	1 x 1mm (BB018-05)	NDS DS 	✓ BB016 - K1	✗
			MTB		BBT476830SSN (Black) Other colours are available	 96.5mm	1 x 2.5mm (BB018-04)	2 x 2.5mm (BB018-04)	NDS DS 	✓ BB016 - K1	✗
	73mm	24mm			BBT476824SSN (Black) Other colours are available	 96.5mm	-	1 x 2.5mm (BB018-04)	NDS DS 	✗	✓ BBSP109
		30mm			BBT476830SSN (Black) Other colours are available	 96.5mm	-	1 x 2.5mm (BB018-04)	NDS DS 	✓ BB016 - K1	✗
	86.5mm	24mm			BBT478624SSN (Black) Other colours are available	 91mm	-	-	NDS DS 	✗	✓ BBSP109
		30mm			BBT478630SSN (Black) Other colours are available	 91mm	-	-	NDS DS 	✓ BB016 - K4	✗
	89.5mm	24mm			BBT478624SSN (Black) Other colours are available	 96.5mm	-	1 x 2.5mm (BB018-04)	NDS DS 	✗	✓ BBSP109
		30mm			BBT478630SSN (Black) Other colours are available	 96.5mm	-	1 x 2.5mm (BB018-04)	NDS DS 	✓ BB016 - K4	✗
	92mm	24mm			BBT478624SSN (Black) Other colours are available	 96.5mm	-	-	NDS DS 	✗	✓ BBSP109
		30mm			BBT478630SSN (Black) Other colours are available	 96.5mm	-	-	NDS DS 	✓ BB016 - K4	✗

BEFORE YOU START:

1

You will need to know the following information to correctly determine the bottom bracket for your needs.

BB Shell Type

- BSA Threaded
- Press Fit Ø46mm
- Press Fit Ø42mm
- Press Fit Ø41mm
- T47 Threaded

BB Width

Measure the dimension over the full width of the frame at the BB. Frame sizes can vary a little but should be ±1mm from one of the sizes detailed in the table inside.

Crankset Axle

You will need to know the axle diameter, the main sizes are:

24mm | 29mm | 30mm

2

You should also check you have the required axle length on your crankset to suit the installed over bearing width of the bottom bracket once installed on your frame. Crank axle types usually fall into the following groups:

Road: To suit 91mm over bearing width. **MTB:** To suit 96.5mm over bearing width. **MTB DH:** To suit 111.5mm over bearing width. **FATBIKE 100:** To suit 128.5mm. **FATBIKE 120:** To suit 148.5mm.